



# Kwik Mix Materials Limited

**Head Office**  
KWIK MIX MATERIALS  
LIMITED  
P.O. Box 520  
Port Colborne, ON L3K 5X7

## Material Safety Data Sheet

### Section 1 – Product and Company Identification

**Product Identifier:** Kwik Mix Asphalt Patch

**Province:** Ontario

**Product Use:** Pavement Repair

**Phone Number:** 905-834-6177

**Manufacturer's Name:** Kwik Mix Materials Limited

**Postal Code:** L3K 5V4

**Street Address:** PO Box 520

**City:** Wainfleet

### Section 2 – Composition/Information on Ingredients

Component	%	CAS Number	LD <sub>50</sub> Of ingredient	LC <sub>50</sub> Of Ingredient
Aggregate	90-95	N/A	N/A	N/A
Asphalt Cement	5	8052-42-4	N/A	N/A
Aliphatic Acid	2	N/A	N/A	N/A
Crystalline Silica	varies	14808-60-7	50m	N/A

### Section 3 – Hazardous Identification

**Relevant Routes of Exposure:** Eye contact, skin contact, inhalation and ingestion

**Effects resulting from EYE contact:** Exposure to airborne dust may cause immediate or delayed irritation or inflammation

**Effects resulting from SKIN contact:** Discomfort or pain cannot be relied upon to alert a person to hazardous skin exposure. Consequently, the only effective means of avoiding skin injury or illness involves minimizing skin contact, particularly contact with wet material. Exposed persons may not feel discomfort until hours after the exposure has ended.

Exposure to material may cause drying of the skin with consequent mild irritation or more significant effects attributable to aggravation of other conditions. If heated, hot product damage may result in severe thermal burns.

August 1, 2014

**Effects resulting from INHALATION (chronic):** Kwik Mix Asphalt Patch may contain crystalline silica. Prolonged exposure to airborne free crystalline silica may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease.

**(acute):** Materials may release irritating fumes or vapours such as smoke, carbon dioxide, and carbon monoxide. Hydrogen Sulfide and other sulfur-containing gases can evolve from this product at elevated temperatures. Exposure to fumes may cause irritation of the nose, eyes or throat.

**Effects resulting from INGESTION:** Although ingestion of small quantities of material is not known to be harmful, ill effects are possible especially if larger quantities are consumed. Do not eat. Ingestion of larger amounts may result in nausea, vomiting, or diarrhoea. Stomach obstructions have been reported in people who have chewed and consumed asphalt.

**Medical conditions which may be aggravated by inhalation or dermal exposure:**

Pre-existing upper respiratory and lung diseases; Unusual hyper-sensitivity to hexavalent chromium salts.

**Section 4 – First Aid**

**Eyes:** Immediately flush eyes with water. Continue flushing eye for at least 15 minutes including under lids to remove all particles. Call a physician immediately.

**Skin:** Wash skin with cool water and pH-neutral soap or a mild detergent intended for use on skin. Seek medical treatment in all cases of prolonged exposure to wet cement or cement mixtures, or prolonged wet skin exposure to dry material.

**Inhalation or Airborne Dust:** Remove to fresh air. Seek medical help if coughing and other symptoms do not subside. May cause irritation or burns.

**Ingestion:** Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately. May cause irritation or burns.

**Section 5 – Fire and Explosion Data**

Combustible solid. Avoid Breathing in fumes.

<b>Flash Point:</b> Not Applicable	<b>Upper Explosive Limit:</b> Not Applicable
<b>Auto Ignition Temperature:</b> Not Applicable	<b>Lower Explosive Limit:</b> Not Applicable
<b>Auto Ignition Temperature:</b> Not Applicable	<b>Extinguishing media:</b> Not Applicable
<b>Hazardous Combustion Products:</b> NO <sub>x</sub> , CO <sub>2</sub> , CO, SO <sub>x</sub>	<b>Unusual fire and explosion hazards:</b> Not Applicable
<b>Special fire fighting procedures:</b> N/A	

---

---

## Section 6- Accidental Release Measures

Collect material using a shovel or a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of fumes and contact with skin. Wear appropriate person protective equipment as described in Section 8.

If wet, scoop up and place in appropriate storage area or container. Allow material to dry before disposal. Dispose of material according to local, provincial, or federal regulations.

## Section 7 – Handling and Storage

Keep material as dry as possible until used. Normal temperatures and pressures do not affect the material. Promptly remove dusty clothing, or clothing that is wet with material.

## Section 8 – Exposure Control/Personal Protection

**Skin protection:** Prevention is essential to avoid potentially severe skin injury. Avoid contact with wet products. If contact occurs, promptly wash affected area with soap and water. Wear impervious clothing and gloves to eliminate skin contact. Where required, wear boots that are impervious to water to eliminate foot and ankle exposure

Periodically wash areas contacted by dry material or wet material with a pH neutral soap. Wash again at the end of the work. If irritation occurs, promptly wash the affected area and seek treatment. If clothing becomes irritated with wet material, it should be removed and replaced with dry clothing.

**Respiratory protection:** Use local or general ventilation to control exposures below applicable exposure limits. Personal respiratory devices are also recommended.

**Ventilation:** Local exhaust or general dilution ventilation to control exposure within applicable limits.

**Eye protection:** When engaged in activities where material could contact the eye, wear safety glasses with side shields or goggles. In unpredictable environments, wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with asphalt products.

## Section 9 – Physical and Chemical Properties

<b>Physical State:</b> Solid	<b>Odour and Appearance:</b> Black Solid	<b>Odour Threshold:</b> Not Applicable
<b>Specific Gravity:</b> 2.6-2.8	<b>Vapour Density:</b> Not Applicable	<b>Vapour Pressure:</b> Not Applicable
<b>Evaporation rate:</b> Not Applicable	<b>Boiling Point:</b> 295-705 Degrees C	<b>Freezing Point:</b> Not Applicable
<b>pH:</b> N/A	<b>Coefficient of Water:</b> Not Applicable	<b>Solubility (in water):</b> Insoluble

## Section 10 – Stability and Reactivity

**Stability:** Stable

**Conditions to avoid:** Excessive Heat

**Incompatibility:** Strong acids or bases.

**Hazardous decomposition:** When heated may liberate Hydrogen Sulfide.

**Hazardous polymerization:** Will not occur.

## Section 11 – Toxicological Information

- Route of Entry – Section 3
- Effects of acute exposure – Section 3
- Effects of chronic exposure to product – Section 3
- Exposure limits – Section 3
- Irritancy of product – Section 3
- Sensitization to product – Section 3
- Carcinogenicity – Section 3
- Toxicological synergistic products – Section 3, 16

## Section 12 – Ecological Information

**Ecotoxicity:** No recognized unusual toxicity to plants or animals.

**Relevant physical and chemical properties:** See sections 9, and 10.

---

Dispense of waste material according to local, provincial and federal regulations. Disposal of bags in an approved landfill or inclinitor

#### **Section 14 – Transportation Data**

**Proper Shipping Name:** Kwik Mix Asphalt Patch

**Hazard class:** Not applicable

**Identification:** Not applicable

**Required label text:** Not applicable

**Hazardous substances:** Not applicable

#### **Section 15 – Other regulatory Information**

**WHMIS Classification:** Considered to be hazardous material under the HPA as defined by the CPR.

**OSHA** – Not applicable

**SARA** – This product contains none of the products subject to reporting requirements.

**TSCA** – Some substances are on the TSCA inventory list.

#### **Section 16 – Other Information**

**Abbreviations:**

**OSHA** – Occupational Safety and Health Administration

**WHMIS** – Workplace Hazardous Material Information System